SAFETY DATA SHEET (SDS)

ISSUED DATE: 20 Nov. 2012 REVISION DATE: 21 Apr. 2025

Product Name and Corporate Information

Product name : ALPOLIC™/fr RF (Reflective Finish Aluminum Composite Material with fire-retardant core)

Name of manufacture : Mitsubishi Chemical Infratec Co., Ltd.

Address : 1-1-1, Marunouchi, Chiyoda-ku, Tokyo 100-8251 Japan

Name of division : ALPOLIC Business Unit

Responsible department : Global Management Department

Phone number : +81-3-6748-7348
E-mail : info@alpolic.jp
Emergency phone number : +81-3-6748-7348
SDS No. : ELL76-0015
Recommended use : Interior material

Restriction on use : Without recommended use

2. Hazardous Identification

GHS classification : Not applicable to hazardous classification

GHS label elements : Not applicable
Symbols : Not applicable
Signal word : Not applicable
Hazard statements : Not applicable
Precautionary statements : Not applicable

Hazard not to applicable to

Wear appropriate protective equipment.

the GHS classification -Particles involved in mechanic

-Particles involved in mechanical processing may irritate mucosal of respiration

apparatus, eyes, mouth, nose, and etc.

-The edges or corners of the material may cut person's body.

-A heated product may cause a burn injury.

Composition / Information on Ingredients

Substance / Mixture : Other (Article)

Chemical name or common name

: Aluminum Composite Material

No.	Ingredients	CAS RN®
1	Aluminum	7429-90-5
2	Polyethylene	9002-88-4
3	Inorganic filler	Not released
4	Coating on the reverse side	Not released
5	Protective film	Not released

^{*}Components less than 0.1 wt% are not shown in the above.

Identification in accordance with UN: Not defined in identifications in UN

Other : Not applicable to the GHS classification for "Article", but listed it about chemical substance.

4. First-Aid Measures

Inhalation : When having inhaled a large quantity of powder and/or particle during mechanical

processing of the product, move to fresh air, to ensure rest and keep warm, and get

medical attention immediately.

Λ1		IC™	/£	DE
ΑI	PO	1(;	/tr	КĿ

MITSUBISHI CHEMICAL INFRATEC CO., LTD.

21 April 2025

Skin contact

In case of slight burns due to heated product, flush out affected part with large amount of water immediately, to cool down the affected part. In case of serious burns, get medical

check immediately.

Eye contact

When eyes are hurt with particle and/or powder during mechanical processing of the product, rinse affected eyes with clean running water. If irritation is persistent afterwards,

get ophthalmic check immediately.

Ingestion

: When having ingested a large quantity of powder and/or particles during mechanical processing of the product, get medical check immediately.

5. Fire-Fighting Measures

Suitable extinguishing media

Unsuitable extinguishing

media

Specific extinguishing

methods

: Water, carbon dioxide, dry-chemical powder and foam fire extinguisher.

: No Information

 $: \;$ In case of occurrence of fire near by the product, cover the products with incombustible

sheet or dry sand, to prevent from fire spread to the products.

If the product is ignited, it is effective for initial extinguishing to dash water. Fire fighting shall be done from the lower portion of the products, and then to upper portion. Fire fighting shall be done from windward side with wearing air-breathing apparatus.

6. Accidental Release Measures

Personal precautions,

protective equipment and emergency procedures Environmental precautions

Methods and material for containment and cleaning up

: Not applicable.

Generally, the product is unlikely to spill out accidentally, because of solid nature.

Same as above.Same as above.

7. Handling and Storage

Handling

: Because you may be injured at the edges or corners of the product, wear gloves, working

clothes and safety shoes.

When you work on piling over again and peeling protection film from the product, you do not handle it in flammable atmosphere because static electricity (spark) is generated. When you handle the product at the time of a strong wind outside, you may lose the

balance or it may be blown off.

Because there is the heavy product depending on product brands or dimensions, you must

be careful about low back pain and the dropping of it.

Storage : Store horizontally where the products can be piled up without deflection. Do not wet the

product with rain. Keep it away from such chemicals as acid, alkali, strong oxidizer and

chlorides, organic solvents, spark and fire.

8. Exposure Controls / Personal Protection

Permissible content

Normally, control is not required. But, when a large quantity of powder and particles are likely to occur due to mechanical processing of the product, apply the following standards as a reference value.

Japan Society of Occupational Health

Ingredient

: Aluminum particle

Inhalable dust 0.5 mg/m3

Recommendation of Occupational Exposure Limits,

Total dust 2 mg/m3

ACGIH

Ingredient

: Aluminum metal and insoluble compound

TLV-TWA* 1 mg/m3 Respiratory fraction ACGIH, 2015 Edition

2018 Edition

* TWA (Time Weighted Average)

Unless special remark is indicated, long term work consisting of 8hrs per day and 5 days per week is available under the above condition.

Facility measures

: When the particle content cannot be maintained within the permissible range, provide such a suitable facility as partial ventilation.

Personal protective equipment

Respiratory protection

: When particle and small chips exist in certain range, wear respirator.

Hands protection : Wear gloves to protect hands from scratch and cut with panel edges.

Eye protection : When operators are exposed to particles and small chips, wear protection glasses during

the operation.

Skin and body protection : Wear working clothes and safety shoes.

Notes

Other : Under normal handling conditions, there is usually no possibility of the exposure in the

product.

9. Physical and Chemical Properties

Appearance (State of matter, Shape, Color, and etc.)

State of matter : Solid

Shape : Panel of 3mm thick

Color : The top surface is an anodized reflective finish and a service coating is

applied on the reverse side.

Smell : None

Melting / Freezing point : No Information Initial boiling point and boiling : No Information

range

Flash point : No Information Flammability (solid) : No Information

Specific gravity : 2.7g/cm³ in aluminum

0.90 to 0.97g/cm³ in polyethylene

Solubility : Insoluble in water
Auto-ignition temperature : No Information
Decomposition temperature : No Information

Stability and Reactivity

Reactivity : Not reaction at normal temperature under normal pressure.

Chemical stability : Stable under normal handling condition.

Possibility of hazardous

reactions

: No Information

Condition to avoid : No Information Incompatible materials : No Information Hazardous decomposition : No Information

products

11. Toxicological Information

No Information

12. Ecological Information

Eco-toxicity : No Information
Persistence and degradability : No Information
Bioaccumulative potential : No Information
Mobility in soil : No Information
Hazardous to the ozone Layer : No Information

13. Disposal Considerations

In accordance with official regulations for waste disposal, dispose by incineration or reclamation as factory waste.

14. Transport Information

International rule : Not applicable in the United Nations Recommendations on the Transport of Dangerous

Goods.
UN Number: -

Other : The product is packed in wooden crate for transportation. During transportation, please

prevent the product from being wet.

15. Regulatory Information

Regulatory information with regard to this product in your country or in your region should be examined by your own responsibility.

16. Other Information

References cited

[1] This SDS based on the SDS of raw materials to contain.

Department issuing SDS

Name of Manufacture: Mitsubishi Chemical Infratec Co., Ltd.

Other

The information contained herein is based on data currently considered accurate. No warranty, however, is expressed or implied regarding the accuracy of these data or the results to be obtained from the use thereof. Mitsubishi Chemical Infratec Co., Ltd. and any associated companies assume no responsibility for personal injury or property damage to vendees, users or third parties caused by the material. Such vendees or users assume all risks associated with use of the material.